

EUROLITE LED PAR-64 HCL Hypno floor bl

PAR spot with 7 x 12 W 6in1 LED (RGBAW&UV) and 3 RGB hypno rings

Art. No.: 51914024

GTIN: 4026397621914



Features:

- 7 high-power 12 W 6in1 LEDs for RGBAW color mixing and blacklight
- 3 concentric hypno rings with altogether 120 RGB LEDs provide fast, dynamic ring effects
- Individual control of center RGBAW+UV LEDs and each RGB ring for spectacular animations
- Built-in auto and music show programs
- Direct color selection for 20 preset colors
- Stepless color blend, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Swivel mounting bracket
- Additional bracket for floor use
- IEC terminals for power linking up to 8 units
- Silver or black housing available
- 120 LEDs 0.5 W SMD 5050 3in1 R/G/B (homogenous color mix)
- 7 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 23°

Logistic

EAN / GTIN: 4026397621914

Weight: 3,22 kg

Length: 0.25 m

Width: 0.25 m

Height: 0.39 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 75 W

Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	120 x 0.5 W SMD 5050 3in1 R/G/B (homogenous color mix) 7 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 6; 7; 24
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	Light J; LED PC-Control 512
Projection:	Flicker-free
Beam angle (1/2 peak):	23°
Beam angle (1/10 peak):	41°
Housing color:	Black
Dimensions:	Width: 29.6 cm Depth: 35.8 cm Height: 22 cm
Weight:	2.68 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x remote control