

EUROLITE LED PAR-64 HCL 12x10W Floor bk

PAR spot with 12 x 10 W 6in1 LED in R, G, B, A, W, UV

Art. No.: 51914027

GTIN: 4026397576610



The article is no longer in our assortment.

Features:

- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- 3 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x6; Light Captain
- With a beam angle of 33°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397576610

Weight: 3,40 kg

Length: 0.25 m

Width: 0.26 m

Height: 0.39 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 125 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	4; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light via microphone; IR remote control
Preprogrammed in:	Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x6; Light Captain
Beam angle:	33°
Beam angle (1/2 peak):	33°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 29,6 cm Depth: 27,7 cm Height: 37,5 cm
Weight:	2,80 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in