

EUROLITE LED IP T-Bar 16 QCL Bar

Weather-proof (IP65) bar with RGBW color mixing, incl. IR remote control

Art. No.: 51914107

GTIN: 4026397680959



Features:

- 16 LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; master/slave function; stand-alone; IR remote control
- Fixtures available for Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 20°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; restaurants, bars and hotels; theater; rental
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397680959
Weight: 6,50 kg
Length: 1.05 m
Width: 0.14 m
Heigh: 0.17 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP65

Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug
Power output:	IP T-Con (F)
Lamp type:	LED lamp
LED type:	16 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.8 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) IP
DMX output:	3-pin XLR (F) IP
Cooling:	Passive convection cooling
Control:	DMX; master/slave function; stand-alone; IR remote control
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 106.50 cm Depth: 10.00 cm Height: 12.65 cm
Weight:	5.95 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 2 x mounting bracket
 2 x screw
 2 x washer