

EUROLITE LED IP T2000 HCL Bar

Weather-proof bar (IP65) with 16 x 10 W 6in1 LED (RGBWA+UV), 100 cm

Art. No.: 51914118

GTIN: 4026397605877



The article is no longer in our assortment.

Features:

- Equipped with 18 high-power 6in1 LEDs in the colors red, green, blue, amber, white and UV
- 4, 5, 6, 7, 9 or 12 DMX channels selectable
- For architectural lighting
- Suitable for external use (IP65)
- Stepless RGBAW+UV color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 18 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 30°
- Suitable for outdoor use IP65

Package contents

Logistic

EAN / GTIN: 4026397605877

Weight: 7,05 kg

Length: 1.08 m

Width: 0.20 m

Height: 0.15 m

- 1 x adapter cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED:	18 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 5; 6; 7; 9; 12
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Projection:	Flicker-free
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Black
Dimensions:	Length: 1,01 m Depth: 17 cm Height: 10,1 cm
Weight:	6,30 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting