

## EUROLITE LED IP T2000 HCL Bar

Weather-proof bar (IP65) with 16 x 10 W 6in1 LED (RGBWA+UV), 100 cm

Art. No.: 51914118

GTIN: 4026397605877



### Features:

- Equipped with 18 high-power 6in1 LEDs in the colors red, green, blue, amber, white and UV
- 4, 5, 6, 7, 9 or 12 DMX channels selectable
- For architectural lighting
- Suitable for external use (IP65)
- Stepless RGBAW+UV color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 18 LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Flicker-free
- With a beam angle of 30°
- Suitable for outdoor use IP65

### Logistic

EAN / GTIN: 4026397605877

Weight: 7,05 kg

Length: 1.08 m

Width: 0.20 m

Height: 0.15 m

## Technical specifications:

---

|                        |   |
|------------------------|---|
| Power supply:          | 100-240 V AC, 50/60 Hz  |
| Power consumption:     | 140 W   |
| IP classification:     | IP65  |
| Power connection:      | Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided) |
| Power output:          | 1 x 3-pin screw plug connector (F) IP   |
| Lamp type:             | LED lamp  |
| LED type:              | 18 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)                                   |
| Flash rate:            | 0 - 18 Hz   |
| DMX channels:          | 4; 5; 6; 7; 9; 12   |
| DMX input:             | 1 x 3-pin screw plug connector (M) IP   |
| DMX output:            | 1 x 3-pin screw plug connector (F) IP   |
| Cooling:               | Passive convection cooling  |
| Control:               | Stand-alone; DMX  |
| Projection:            | Flicker-free  |
| Beam angle:            | 30°   |
| Beam angle (1/2 peak): | 30°   |
| Housing color:         | Black   |
| Dimensions:            | Length: 101 cm<br>Depth: 17 cm<br>Height: 10.1 cm   |
| Weight:                | 6.30 kg   |
| Special product:       | Not designed for household room illumination  |
| Intended use:          | Show effect lighting  |

## Scope of delivery:

---

1 x adapter cable