

EUROLITE LED IP T1000 HCL 9x12W

Weather-proof bar (IP65) with 9 x 12 W 6in1 LED (RGBAW+UV), 52 cm

Art. No.: 51914121

GTIN: 4026397558050



The article is no longer in our assortment.

Features:

- Equipped with 9 high-power 6in1LEDs in the colors red, green, blue, amber, white and UV
- For architectural lighting
- Suitable for external use (IP65)
- Stepless RGBAW+UV color mixture
- Dimmer
- Different dimmer curves and dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Random strobe effect
- Preset colors and color temperatures
- Internal programs
- Programmable color change speed
- Programmed and programmable chaser
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- 9 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- The device is cooled by passive convection cooling
- Control via DMX
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1
- Flicker-free
- With a beam angle of 30°
- Suitable for outdoor use IP65

Package contents

Logistic

EAN / GTIN: 4026397558050

Weight: 5,00 kg

Length: 0.65 m

Width: 0.21 m

Height: 0.16 m

- 1 x adapter cable

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
LED:	9 x 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 18 Hz
DMX channels:	4; 5; 6; 7; 9; 12
DMX input:	1 x 3-pin screw plug connector (M) IP
DMX output:	1 x 3-pin screw plug connector (F) IP
Cooling:	Passive convection cooling
Control:	DMX
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1
Projection:	Flicker-free
Beam angle:	30°
Beam angle (1/2 peak):	30°
Housing color:	Black
Dimensions:	Length: 58,5 cm Depth: 18,5 cm Height: 10 cm
Weight:	4,60 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting