


## EUROLITE LED IP Flood RGB 10mm 20°

LED RGB outdoor floodlight (IP65)

Art. No.: 51914125

GTIN: 4026397294279



**The article is no longer in our assortment.**

### Description:

In front of buildings or public places, the LED-PAR-64 and the LED floodlight are in real good hands. The colors are static and change automatically. Due to the LED technology, the LEDs shine amazingly bright. Moreover, these outdoor spots are able to strobe and thus have an attractive effect in addition to their nine integrated programmes. To not be vulnerable to humidity, DIP switches were set aside. The spots can be linked and completely managed via a remote control.

### Logistic

EAN / GTIN: 4026397294279

Weight: 4,60 kg

Length: 0.34 m

Width: 0.24 m

Height: 0.28 m

### Features:

- Functions: static colors; automatic color change, 9 built-in programs and strobe effect with variable speed; Master/Slave
- Control in stand-alone mode and DMX programming via optional IR remote (necessary for use)
- DMX control via regular DMX controller (occupies 5 channels)
- Ideal LED luminary for outdoor use
- Locking possibility at the mounting bracket
- Perfect for public places and buildings
- 215 high-power 10mm LEDs
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Ready for connection with power cord and safety power plug
- Available in 20° or in 40° versions of the LED beam angle
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Preprogrammed in Light´J
- Suitable for outdoor use IP65
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	24 W
IP classification:	IP65
Lamp type:	LED lamp
DMX channels:	5
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Preprogrammed in:	Light'J
Beam angle (1/2 peak):	20°
Housing color:	Grey
Dimensions:	Width: 30 cm Depth: 17,5 cm Height: 21 cm
Weight:	4,10 kg
DMX channels:	5
DMX connection:	3-pin XLR
Protection grade:	IP65
LED number:	215
LED type:	10 mm
Beam angle:	20°
Dimensions (LxHxW):	300 x 210 x 175mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting