

EUROLITE LED IP PAD 60x3W CW/WW

Weather-proof DMX spotlight (IP65) with 40 x 3 W LED (cold and warm white)

Art. No.: 51914164 GTIN: 4026397461688











The article is no longer in our assortment.

Features:

- Equipped with 60 x 3 W LED: 24 x warm white, 36 x cold white
- For architectural lighting
- Suitable for external use (IP65)
- Color temperature steplessly adjustable between 3000 K and 7000 K
- 17 preset color temperatures
- Strobe effect
- Dimmer
- Master/Slave function
- Compact, matt grey housing
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Infrared remote control in credit card format included in delivery
- Switch-mode power supply, automatic power supply adaption between 100 and 240 volts without power selector
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- 60 powerful LEDs 3 W high-power 2in1 BCL CW/WW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control
- Preprogrammed in Light'J; LED PC-Control 512
- With a beam angle of 45°
- Suitable for outdoor use IP65
- Silent operation

Package contents

Logistic

EAN / GTIN: 4026397461688

Weight: 9,50 kg Length: 0.39 m Width: 0.23 m Heigth: 0.43 m

Technical specifications:

| Power supply: | 100-240 V AC, 50/60 Hz |
|------------------------|---|
| Power consumption: | 160 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided) |
| Cable length: | 1,5 m |
| Power output: | 1 x 3-pin screw plug connector (F) IP |
| Lamp type: | LED lamp |
| LED: | 60 x 3 W high-power 2in1 BCL CW/WW (homogenous color mix) |
| Flash rate: | 1 - 30 Hz |
| DMX channels: | 2; 5 |
| DMX input: | 1 x 3-pin screw plug connector (M) IP |
| DMX output: | 1 x 3-pin screw plug connector (F) IP |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; IR remote control |
| Preprogrammed in: | Light'J; LED PC-Control 512 |
| Beam angle: | 45° |
| Beam angle (1/2 peak): | 45° |
| Housing color: | Grey |
| Dimensions: | Width: 34,4 cm |
| | Depth: 14 cm |
| | Height: 32,6 cm |
| Weight: | 8,40 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR1225 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
| | |