

## EUROLITE LED IP Tourlight 120 QCL

Weather-proof LED spotlight (IP65) with 120 W RGBW LED

Art. No.: 51914250

GTIN: 4026397661903



### Features:

- High-performance LED spot for outdoor applications
- Equipped with a 120-watt RGBW COB LED
- Chip-on-board technology makes for homogeneous color mixing
- Beam angle: 11° (1/2 peak), 26° (1/10 peak)
- For architectural and stage lighting
- Weather-proof metal housing (IP65)
- Stepless RGBW color blend, color change, color fade, dimmer and strobe effect
- 63 integrated color macros
- User-defined color settings can be set and saved individually
- Different dimmer curves and dimmer speeds (step response) adjustable
- DMX-controlled operation or stand-alone operation with master/slave function
- Addressing and setting via control board with four touch operating buttons and LCD
- Swivel mounting bracket
- Additional bracket for floor use
- Hanging installation via quick-lock Omega holder (included in delivery)
- IP T-Con terminals for power linking up to 8 units
- 1 LED 120 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- The device is cooled by temperature-controlled fan
- Control via master/slave function; stand-alone
- Flicker-free
- With a beam angle of 11°
- Suitable for outdoor use IP65

### Logistic

EAN / GTIN: 4026397661903

Weight: 6,60 kg

Length: 0.26 m

Width: 0.26 m

Height: 0.45 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
DMX channels:	1; 4; 8; 9
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Temperature-controlled fan
Control:	Master/slave function; stand-alone
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	26°
Housing color:	Black
Dimensions:	Width: 27 cm Depth: 27 cm Height: 30.5 cm
Weight:	5.90 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

1 x spotlight  
1 x user manual  
1 x power cord  
1 x omega bracket  
1 x cover