

## EUROLITE LED IP TL-3 QCL Trusslight

Weather-proof LED spot (IP65) ideal as trusslight or uplight with bright 3x10W RGBW LED

Art. No.: 51914270

GTIN: 4026397727333



List price: 296.31 €

incl. 19% VAT.

### Features:

- Compact and bright
- 3 powerful LEDs 10 W 4in1 QCL RGBW (homogenous color mix)
- Additional frost filter provides a wide, soft and homogeneous light
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance
- Uplight effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- Control via stand-alone; DMX; Master/slave function; IR remote control; RDM
- 3 buttons on the remote control for saving your own settings
- With a beam angle of 10°
- Flicker-free
- OLED display
- Mains input and output for power linking up to 8 units
- The device is cooled by passive convection cooling
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; video and photography
- Silent operation
- Application possibility: Standing; suspended
- Threaded inserts for suspended installation
- Preprogrammed in EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light J
- Built with SEETRONIC connector

### Package contents

### Logistic

EAN / GTIN: 4026397727333

Weight: 2,12 kg

Length: 0.20 m

Width: 0.18 m

Height: 0.20 m

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x diffusor cover, 1 x remote control, 1 x battery, 3 x knurled screw

## Technical specifications:

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz  |
| Power consumption:      | 30 W  |
| IP classification:      | IP65  |
| Protection class:       | Protection class I  |
| Power connection:       | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)                 |
| Power output:           | IP T-Con (F) mounting version   |
| Lamp type:              | LED lamp  |
| LED:                    | 3 x 10 W 4in1 QCL RGBW (homogenous color mix)   |
| Flash rate:             | 1 - 23 Hz   |
| DMX channels:           | 3; 4; 6; 8; 11  |
| DMX input:              | 3-pin XLR (M) mounting version IP   |
| DMX output:             | 3-pin XLR (F) mounting version IP   |
| Cooling:                | Passive convection cooling  |
| Control:                | Stand-alone; DMX; Master/slave function; IR remote control; RDM   |
| Preprogrammed in:       | EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light Captain; Light J |
| Projection:             | Flicker-free  |
| Beam angle:             | 10°   |
| Beam angle (1/2 peak):  | 10°<br>Frost filter 20°   |
| Beam angle (1/10 peak): | 20°<br>Frost filter 45°   |
| Housing color:          | Black   |
| Attachment system:      | 2x M10 thread   |
| Display type:           | OLED display  |
| Use of brands:          | Built with SEETRONIC connector  |
| Dimensions:             | Length: 13,1 cm<br>Depth: 11,8 cm<br>Height: 15,3 cm  |
| Weight:                 | 1,90 kg   |
| Noise classification:   | Class 0 (no noise at all)   |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination  |
| Intended use:           | Show effect lighting  |