

EUROLITE LED IP FL-10 6000K SLIM

Flat IP65 outdoor floodlight with 20 SMD-LEDs cold white (CW)

Art. No.: 51914710 GTIN: 4026397561104







List price: 23.68 €

incl. 19% VAT.

Features:

- Add highlights to your house and garden
- Extremely slim housing in an appealing design
- 20 powerful LEDs SMD cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 120°
- Good color rendering index (CRI)
- With Mounting bracket
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

Package contents

1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	10 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug

Logistic

EAN / GTIN: 4026397561104

Weight: 0,55 kg Length: 0.14 m Width: 0.13 m Heigth: 0.07 m

LED: 20 x SMD cold white (CW) Color of light: Cold white CW >5000 K Color temperature: 6000K Cooling: Passive convection cooling Control: Plug and play Beam angle: 120° Beam angle (1/2 peak): 120° Color rendering index (CRI): 82 Ra Housing color: White Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F Cable length: Approx. 1 m	Lamp type:	LED lamp
Color temperature: Cooling: Passive convection cooling Control: Plug and play Beam angle: 120° Beam angle (1/2 peak): 120° Color rendering index (CRI): 82 Ra Housing color: White Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	LED:	20 x SMD cold white (CW)
Cooling: Passive convection cooling Control: Plug and play Beam angle: 120° Beam angle (1/2 peak): 120° Color rendering index (CRI): 82 Ra Housing color: White Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Color of light:	Cold white CW >5000 K
Control: Beam angle: 120° Beam angle (1/2 peak): Color rendering index (CRI): Housing color: White Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Color temperature:	6000K
Beam angle: 120° Beam angle (1/2 peak): 120° Color rendering index (CRI): 82 Ra Housing color: White Attachment system: Mounting bracket Material: Aluminum casting Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Cooling:	Passive convection cooling
Beam angle (1/2 peak): Color rendering index (CRI): Housing color: White Attachment system: Material: Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Control:	Plug and play
Color rendering index (CRI): Housing color: White Attachment system: Material: Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: S20 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Beam angle:	120°
Housing color: Attachment system: Material: Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Beam angle (1/2 peak):	120°
Attachment system: Material: Aluminum casting Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Color rendering index (CRI):	82 Ra
Material: Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Housing color:	White
Dimensions: Width: 11,8 cm Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Attachment system:	Mounting bracket
Depth: 3,2 cm Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Material:	Aluminum casting
Height: 11,9 cm Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Dimensions:	Width: 11,8 cm
Weight: 520 g Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F		Depth: 3,2 cm
Noise classification: Class 0 (no noise at all); Class 0 (no noise at all) Power cord Cable construction: 3 x 1,0 mm² H05RN-F		Height: 11,9 cm
Power cord Cable construction: 3 x 1,0 mm² H05RN-F	Weight:	520 g
Cable construction: 3 x 1,0 mm² H05RN-F	Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
· · · · · · · · · · · · · · · · · · ·	Power cord	
Cable length: Approx. 1 m	Cable construction:	3 x 1,0 mm² H05RN-F
	Cable length:	Approx. 1 m
Color: Black	Color:	Black
Mounting bracket	Mounting bracket	
Diameter mounting holes: 1 x Ø7mm; 2 x Ø6mm	Diameter mounting holes:	1 x Ø7mm; 2 x Ø6mm
Material: Metal, 1 mm	Material:	Metal, 1 mm
Color: White	Color:	White