

EUROLITE LED IP FL-30 SMD uv

Flat IP65 outdoor floodlight with 60 SMD-LEDs ultra violet (UV)

Art. No.: 51914966

GTIN: 4026397676822



Features:

- 60 LEDs 0.5 W SMD 5730 ultra violet (UV)
- UV effect
- The device is cooled by passive convection cooling
- Control via plug and play
- With mounting bracket
- Suitable for outdoor use IP65
- Various versions available
- Silent operation
- For application areas such as: Decoration; party room; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Suspended

Logistic

EAN / GTIN: 4026397676822

Weight: 1,10 kg

Length: 0.25 m

Width: 0.20 m

Height: 0.07 m

Technical specifications:

| | |
|---------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 30 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 1.0 mm ² H05RN-F |
| Cable length: | Approx. 1 m |

| | |
|--------------------------|--|
| Lamp type: | LED lamp |
| LED type: | 60 x 0.5 W SMD 5730 ultra violet (UV) |
| Cooling: | Passive convection cooling |
| Control: | Plug and play |
| Beam angle (1/2 peak): | 80° |
| Beam angle (1/10 peak): | 120° |
| Color of light: | UV-reflecting |
| Wavelength: | Ultra violet (UV) 374 nm |
| Housing color: | Black matte |
| Attachment system: | Mounting bracket |
| Material: | Aluminum casting |
| Dimensions: | Width: 22 cm Depth: 3.5 cm Height: 17.8 cm |
| Weight: | 1.01 kg |
| Noise classification: | Class 0 (no noise at all) |
| Diameter mounting holes: | 3 x Ø8mm |
| Material: | Metal, 2 mm |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

1 x spotlight
1 x user manual