

EUROLITE LED IP FL-50 SMD WW

Flat outdoor floodlight (IP66) with white SMD LEDs


Art. No.: 51915030 GTIN: 4026397695908











incl. 19% VAT.

Features:

- 64 powerful LEDs SMD 2835 warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

Package contents

1 x device, 1 x user manual

Logistic

EAN / GTIN: 4026397695908

Weight: 0,70 kg Length: 0.21 m Width: 0.07 m Heigth: 0.17 m

Technical specifications:

230 V AC, 50 Hz
50 W
IP66
Protection class I
Fixed power supply cord with safety plug
3 x 1,0 mm² H05RN-F
Approx. 1 m

Lamp type:	LED lamp
LED type:	64 x SMD 2835 warm white (WW)
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color temperature:	3000K
Color rendering index (CRI):	80 Ra
Luminous flux:	4320 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 25 cm
	Depth: 2,6 cm
	Height: 19,2 cm
Weight:	0,63 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
EPREL-Nr:	963861
Mounting bracket	
Diameter mounting holes:	1 x Ø8mm; 2 x Ø6mm
Material:	Metal, 1,5 mm