

EUROLITE LED IP FL-50 SMD CW

Flat outdoor floodlight (IP66) with white SMD LEDs

Art. No.: 51915035

GTIN: 4026397695977



List price: 35.58 €

incl. 19% VAT.

Features:

- 64 powerful LEDs SMD 2835 cold white (CW)
- The device is cooled by passive convection cooling
- Control via plug and play
- Good color rendering index (CRI)
- With Mounting bracket
- Suitable for outdoor use IP66
- Various versions available
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

Package contents

- 1 x device, 1 x user manual

Logistic

EAN / GTIN: 4026397695977

Weight: 0,75 kg

Length: 0.21 m

Width: 0.07 m

Height: 0.17 m

Technical specifications:

Power supply: 230 V AC, 50 Hz

Power consumption: 50 W

IP classification: IP66

Protection class: Protection class I

Power connection: Fixed power supply cord with safety plug

Cable construction: 3 x 1,0 mm² H05RN-F

Cable length: Approx. 1 m

Lamp type:	LED lamp
LED:	64 x SMD 2835 cold white (CW)
Color temperature:	6000K
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color rendering index (CRI):	81 Ra
Luminous flux:	4569 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 25 cm Depth: 2,6 cm Height: 19,2 cm
Weight:	690 g
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	F
Mounting bracket	
Diameter mounting holes:	2 x Ø6mm; 1 x Ø8mm
Material:	Metal, 1,5 mm