

EUROLITE LED SLS-30 COB UV Floor

Compact UV spotlight with 30 W LED, DMX and remote control

Art. No.: 51915303

GTIN: 4026397669305



List price: 117.81 €

incl. 19% VAT.

Features:

- Striking blacklight effect
 - Strobe effect with adjustable speed
 - DMX and power terminals intelligently designed for easy wiring
 - 1 powerful LED 30 W COB (chip-on-board) ultra violet (UV)
 - UV effect; Strobe effect; Wash effect
 - Integrated show programs
 - The device is cooled by cooling fan
 - Control via IR remote control; DMX; Sound to light via Microphone; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - Preprogrammed in Light´J; Light Captain
 - Flicker-free
 - With a beam angle of 18°
 - With double bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397669305
Weight: 1,30 kg
Length: 0.19 m
Width: 0.19 m
Height: 0.24 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

| | |
|--------------------------|--|
| Power consumption: | 20 W |
| IP classification: | IP20 |
| Protection class: | Protection class II |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug included |
| Power output: | IEC connector (F) mounting version |
| Fuse: | 5 x 20 mm, T 1 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 1 x 30 W COB (chip-on-board) ultra violet (UV) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 1; 2; 4 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | 1 x cooling fan |
| Control: | IR remote control; DMX; Sound to light via Microphone; stand-alone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light J; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 18° |
| Beam angle (1/2 peak): | 18° |
| Beam angle (1/10 peak): | 65° |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | 4 digit 7-segment LED display |
| Material: | Plastic |
| Dimensions: | Width: 21,5 cm Depth: 12,7 cm Height: 22,8 cm |
| Weight: | 1,10 kg |
| Noise classification: | Class 3 (clearly perceptible sounds); class 3 (clearly perceptible sounds) |
| Photobiological safety: | Risk Group 0 |
| Power cord | |
| Cable construction: | 3 x 0,75 mm ² H05VV-F |
| Cable length: | Approx. 1,2 m |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø11mm; 2 x Ø10mm |
| Material: | Metal, 1,5 mm |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |

Intended use:

Show effect lighting
