

EUROLITE LED SLS-30 COB RGBAL Floor

LED floor spot with 5in1 PCL RGBAL color mixing, incl. IR remote control

Art. No.: 51915304

GTIN: 4026397752410



Description:

This fixture demonstrates that lime color mixing is not limited to high-end models. It is based on a COB LED featuring red, green, blue, amber, and lime.

This allows not only for vibrant, punchy colors but also for excellent yellow and orange tones, as well as convincing white light.

Features:

- 1 LED 30 W COB (chip-on-board) 5in1 PCL RGBAL (homogenous color mix)
- DMX and power terminals intelligently designed for easy wiring
- Dimmer electronic; color blend stepless; color change adjustable; color fade adjustable
- Wash effect; strobe effect
- 5 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; sound to light via microphone; IR remote control; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- DMX fail mode (blackout; hold; full on; static; auto)
- With a beam angle of 25°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; theater

Logistic

EAN / GTIN: 4026397752410

Weight: 1,35 kg

Length: 0.19 m

Width: 0.19 m

Height: 0.24 m

- Very quiet working noise
- Application possibility: Standing; suspended; on stand
- Good color rendering index (CRI)

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	23 W
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) 5in1 PCL RGBAL (homogenous color mix)
Flash rate:	0.5 - 23 Hz
DMX channels:	3; 5; 5; 7; 10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x low-noise cooling fan
Control:	Stand-alone; sound to light via microphone; IR remote control; DMX; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Projection:	Flicker-free
PWM frequency:	3900 Hz
DMX fail mode:	Blackout; hold; full on; static; auto
Beam angle:	25°
Beam angle (1/2 peak):	25°
Beam angle (1/10 peak):	80°
Color rendering index (CRI):	81 Ra
Lamp life:	50000 h
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
USB port:	1 x type A
Diameter mounting holes:	1 x Ø11mm
Material:	Plastic
Dimensions:	Width: 21.5 cm Depth: 12.7 cm Height: 22.85 cm Diameter: Ø 16.8 cm
Weight:	1.15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual