

## EUROLITE LED 7C-7 Silent Slim Spot

Silent 7in1 LED PAR spotlight in a space-saving design

Art. No.: 51915320

GTIN: 4026397645187



### Description:

#### Seven colors in one LED

With this LED spotlight, the name 7C stands for unlimited possibilities for colour design: you have 7 colours available for colour mixing. In addition to red, green and blue, this includes amber, cold white, warm white and UV. No matter which color you want to create, this spotlight leaves nothing to be desired. Even white light can be created with an excellent CRI in any desired color temperature thanks to the color mixing. The headlamps are available in two versions: With 7 or 12 nine watt strong LEDs.

#### Fanless and quiet

But both models have even more advantages: Don't worry about annoying noises - the headlamps do not need a fan. The compact metal housing is very sturdy. The power is connected via a P-Con input and you can also loop the power through to other devices. A USB socket is available for wireless transmission of the DMX signal, into which a wireless Quick DMX receiver can be plugged directly.

### Features:

- Flat version requires minimal space when mounting
- 7 LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)

### Logistic

EAN / GTIN: 4026397645187

Weight: 2,90 kg

Length: 0.30 m

Width: 0.26 m

Height: 0.14 m

- Fixtures available for LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; theater; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

## Technical specifications:

|                              |                                                                                                                                                                                                                          |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:                | 100-240 V AC, 50/60 Hz                                                                                                                                                                                                   |
| Power consumption:           | 45 W                                                                                                                                                                                                                     |
| IP classification:           | IP20                                                                                                                                                                                                                     |
| Protection class:            | Protection class I                                                                                                                                                                                                       |
| Power connection:            | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                                                                                                          |
| Power output:                | 1 x P-Con (gray), mounting version                                                                                                                                                                                       |
| Fuse:                        | 5 x 20 mm, T 1 A fuse replaceable                                                                                                                                                                                        |
| Lamp type:                   | LED lamp                                                                                                                                                                                                                 |
| LED type:                    | 7 x 9 W high-power 7in1 SCL<br>RGB/CW/WW/A/UV (homogenous color mix)                                                                                                                                                     |
| Flash rate:                  | 0 - 20 Hz                                                                                                                                                                                                                |
| DMX channels:                | 3; 4-1; 4-2; 4-3; 4-4; 5; 6; 7; 9; 12                                                                                                                                                                                    |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version                                                                                                                                                                                       |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version                                                                                                                                                                                       |
| Cooling:                     | Passive convection cooling                                                                                                                                                                                               |
| Control:                     | Stand-alone; DMX; IR remote control; sound to<br>light via microphone; master/slave function;<br>QuickDMX via USB (optional); W-DMX by<br>wireless solution via USB (optional); CRMX by<br>LumenRadio via USB (optional) |
| Fixtures available for:      | LED PC-Control 512; EASY SHOW 1; Light<br>Captain; EASY SHOW 2; EASY SHOW 3                                                                                                                                              |
| Projection:                  | Flicker-free                                                                                                                                                                                                             |
| Beam angle:                  | 15°                                                                                                                                                                                                                      |
| Beam angle (1/2 peak):       | 15°                                                                                                                                                                                                                      |
| Beam angle (1/10 peak):      | 33°                                                                                                                                                                                                                      |
| Color rendering index (CRI): | 92 Ra                                                                                                                                                                                                                    |
| Housing color:               | Black matte                                                                                                                                                                                                              |
| Attachment system:           | Double bracket                                                                                                                                                                                                           |
| Display type:                | 4 digit 7-segment LED display                                                                                                                                                                                            |
| USB port:                    | Type A                                                                                                                                                                                                                   |
| Material:                    | Aluminum casting; metal                                                                                                                                                                                                  |
| Dimensions:                  | Width: 22 cm<br>Depth: 11 cm                                                                                                                                                                                             |

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
|                          | Height: 25.5 cm                                         |
| Weight:                  | 2.60 kg                                                 |
| Noise classification:    | Class 0 (no noise at all)                               |
| Photobiological safety:  | Risk Group 0                                            |
| Diameter mounting holes: | 1 x Ø11mm                                               |
| Material:                | Metal, 2.5 mm                                           |
| Cable construction:      | 3 x 1.0 mm² H05VV-F                                     |
| Cable length:            | Approx. 1.2 m                                           |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product:         | Not designed for household room illumination            |
| Intended use:            | Show effect lighting                                    |

### Scope of delivery:

1 x light effect  
 1 x power cord  
 1 x remote control  
 1 x user manual