

## EUROLITE LED SLS-603 TCL + UV Floor

Flat spotlight with 5 x 3 W 3in1 LED (RGB) and one 3 W UV LED, incl. IR remote control

Art. No.: 51915358

GTIN: 4026397561692



**List price: 89.13 €**

incl. 19% VAT.

### Features:

- Slim design for space-saving applications
  - DMX and power terminals intelligently designed for easy wiring
  - 6 powerful LEDs 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
  - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
  - UV effect; Strobe effect
  - Integrated show programs
  - The device is cooled by cooling fan
  - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
  - With a beam angle of 11°
  - With double bracket
  - 4 digit 7-segment LED display
  - Preprogrammed in Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
  - Mains input and output for power linking up to 8 units
  - Application possibility: Standing; suspended; on stand
  - For application areas such as: Clubs/dancing school; Wedding/gala/events; Party room; mobile djs / entertainer
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397561692  
Weight: 1,67 kg  
Length: 0.25 m  
Width: 0.21 m  
Height: 0.13 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	20 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	6 x 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
DMX channels:	4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
Preprogrammed in:	Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	28°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic; metal; ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 23 cm Depth: 11 cm Height: 23 cm
Weight:	1,41 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,1 m
Mounting bracket	
Diameter mounting holes:	5 x Ø11mm
Material:	Metal, 2 mm
Color:	Black
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting