

## EUROLITE LED SLS-180 RGB 18x1W Floor

Flat spotlight with 18 x 1 W LED in R, G, B

Art. No.: 51915375

GTIN: 4026397506235



**The article is no longer in our assortment.**

### Features:

- Equipped with 18 x 1 W LED: 6 x red, 6 x green, 6 x blue
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Additional rubber feet when the spot shall be positioned on the floor without mounting bracket
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, three different color changes (2 x FC\*, 1 x SC+) with adjustable speed, RGB color mixture, strobe effect, dimmer
- \* FC = Fading Colors: uninterruptedly gradually fades out colors in a given period of time
- + SC = Switching Colors: uninterruptedly switches color in a given period of time
- Memory function
- Master/Slave for parallel operation of several devices
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 18 powerful LEDs 1 W high-power R/G/B (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- With a beam angle of 35°
- 4 digit 7-segment LED display

### Package contents

- 1 x spotlight, 1 x power cord, 1 x user manual

### Logistic

EAN / GTIN: 4026397506235

Weight: 1,47 kg

Length: 0.25 m

Width: 0.21 m

Height: 0.13 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12,00 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	1,4 m
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	18 x 1 W high-power R/G/B (homogenous color mix)
DMX channels:	3; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Beam angle:	35°
Beam angle (1/2 peak):	35°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 21 cm Depth: 10,5 cm Height: 22 cm
Weight:	1,25 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting