

EUROLITE LED SLS-12 QCL Floor

LED floor spot with RGBW color mixing, incl. IR remote control

Art. No.: 51915383

GTIN: 4026397696714



List price: 153.51 €

incl. 19% VAT.

Features:

- Slim design for space-saving applications
- 12 powerful LEDs 8 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 2 integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; stand-alone; Sound to light; DMX; Master/slave function
- With a beam angle of 16°
- With double bracket
- 4 digit 7-segment LED display
- Preprogrammed in EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; Stage; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397696714

Weight: 1,95 kg

Length: 0.23 m

Width: 0.23 m

Height: 0.23 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 40 W

IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A
LED:	12 x 8 W 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 8
Cooling:	1 x cooling fan
Control:	QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control; stand-alone; Sound to light; DMX; Master/slave function
Preprogrammed in:	EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	34
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 26,0 cm Depth: 12,5 cm Height: 23,3 cm
Weight:	1,70 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Remote control	
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting