

## EUROLITE LED TL-4 QCL RGB+UV Trusslight

Variable truss light and uplight with bright 4 x 8 W RGB+UV LED

Art. No.: 51915448

GTIN: 4026397658286



### Features:

- Compact and bright
- Perfect for ALUTRUSS 4 point system QUADLOCK
- Folding foot adjustable in 5 steps for flexible placement
- 4 LEDs 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
- Fixtures available for LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With a beam angle of 13°
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397658286

Weight: 1,70 kg

Length: 0.18 m

Width: 0.18 m

Height: 0.16 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	4 x 8 W high-power 4in1 QCL RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 8
DMX input:	1 x USB, type A 1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; sound to light via microphone; IR remote control; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); stand-alone
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	M10 thread
Display type:	Monochrome 4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Length: 15.5 cm Width: 14.5 cm Height: 13.0 cm
Weight:	1.56 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1.1 m
Color:	Black
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

## Scope of delivery:

1 x spotlight  
1 x power cord  
1 x remote control  
1 x user manual