eurolite®

EUROLITE LED PST-3W 3200K Spot


Narrow beam pinspot with 3 W warm white (WW) LED











incl. 19% VAT.

Features:

- For illuminating e.g. mirror balls, entrance or counter areas or as basic illumination
- 1 powerful LED 3 W high-power warm white (WW)
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 6°
- Good color rendering index (CRI)
- With Mounting bracket
- Various versions available
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; on stand Package contents
- 1 x spotlight, 1 x user manual

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	5 W
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug

Logistic

EAN / GTIN: 4026397649079 Weight: 0,28 kg Length: 0.09 m Width: 0.09 m Heigth: 0.13 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Cable length:	Approx. 0,9 m
Lamp type:	LED lamp
LED:	1 x 3 W high-power warm white (WW)
Color temperature:	3200K
Cooling:	Passive convection cooling
Control:	Plug and play
Beam angle:	6°
Beam angle (1/2 peak):	6°
Color rendering index (CRI):	82 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Plastic
Dimensions:	Width: 9 cm
	Depth: 10 cm
	Height: 10 cm
Weight:	240 g
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	1 x Ø12mm
Material:	Metal, 2 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting