

EUROLITE LED PST-10 QCL spot

LED pinspot with COB LED and DMX control as well as IR remote control

Art. No.: 51916152 GTIN: 4026397690132











List price: 106.98 € incl. 19% VAT.

Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 powerful LED 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; Sound to light via Microphone; Master/slave function
- Flicker-free
- Strobe effect
- With a beam angle of 4°
- With double bracket
- 4 digit 7-segment LED display
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

1 x device, 1 x remote control, 1 x diffusor cover, 1 x lamp clamping ring, 1 x battery, 1 x user

Logistic

EAN / GTIN: 4026397690132

Weight: 1,20 kg Length: 0.15 m Width: 0.15 m Heigth: 0.29 m

Technical specifications:

| Cable length: Approx. 1 m Fuse: 5 x 20 mm, T 0,5 A Lamp type: LED lamp LED: 1 x 10 W COB (chi (homogenous colo) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection IR remote control; light via Microphon | |
|--|--|
| Protection class: |)/60 Hz |
| Protection class: Power connection: Fixed power suppl Cable length: Approx. 1 m Fuse: 5 x 20 mm, T 0,5 A Lamp type: LED lamp LED: 1 x 10 W COB (chi (homogenous colo Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection Control: IR remote control; ight via Microphol ight via Microphol gight via Microphol Beam angle (1/2 peak): Frost filter 16° Beam angle (1/10 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: Noise classification: Photobiological safety: Material: Dimenter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost Frost Plastic, 1 mm Diffusor cover Material: Plastic, 1 mm Diffusor cover | |
| Power connection: Fixed power supplemental power | |
| Cable length: Approx. 1 m Fuse: 5 x 20 mm, T 0,5 A Lamp type: LED lamp LED: 1 x 10 W COB (chi (homogenous color (homoge | I |
| Fuse: 5 x 20 mm, T 0,5 A Lamp type: LED lamp LED: 1 x 10 W COB (chi (homogenous colo (homogenous colo (homogenous colo)) Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection Control: IR remote control; light via Microphor Ilght Captain; EAS EASY SHOW 3 EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at a classification: Photobiological safety: Risk Group 0 Mounting bracket < | oly cord with Euro plug |
| LED lamp LED: 1 x 10 W COB (chi (homogenous colo (homoge | |
| LED: 1 x 10 W COB (chi (homogenous color (homoge | A Fuse replaceable |
| (homogenous color Color temperature: 6500K Flash rate: 0 - 20 Hz DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection Control: IR remote control; light via Microphon Preprogrammed in: Light Captain; EAS EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at the color) Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Flash rate: DMX channels: 3; 4; 5; 6; 9 Cooling: Passive convection: IR remote control; light via Microphon Preprogrammed in: Light Captain; EAS EASY SHOW 3 Projection: Beam angle: Beam angle (1/2 peak): Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise and Metal): Photobiological safety: Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | nip-on-board) 4in1 QCL RGBW or mix) |
| DMX channels: Cooling: Passive convection: IR remote control; light via Microphon Preprogrammed in: Light Captain; EAS EASY SHOW 3 Projection: Beam angle: Beam angle (1/2 peak): Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise a photobiological safety: Material: Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Cooling: Control: IR remote control; light via Microphon Preprogrammed in: Light Captain; EAS EASY SHOW 3 Projection: Beam angle: Beam angle: Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise a light of the properties of the | |
| Control: IR remote control; light via Microphon Preprogrammed in: Light Captain; EAS EASY SHOW 3 Projection: Flicker-free Beam angle: 4° Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise a last Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Preprogrammed in: Light Captain; EAS EASY SHOW 3 Projection: Flicker-free Beam angle: Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise and the properties of the | on cooling |
| Projection: Projection: Beam angle: Beam angle (1/2 peak): Beam angle (1/10 peak): Beam angle (1/2 peak): Spot 7° Frost filter 16° Beam angle (1/2 peak): Beam angle (1/2 peak): Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/2 peak): | ; stand-alone; DMX; Sound to ne; Master/slave function |
| Beam angle: Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise and second peace of the second peace | SY SHOW 2; EASY SHOW 1; |
| Beam angle (1/2 peak): Spot 4° Frost filter 16° Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Beam angle (1/10 peak): Spot 7° Frost filter 36° Housing color: Black Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise a photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Housing color: Housing color: Black Attachment system: Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise and properties) Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Attachment system: Double bracket Display type: 4 digit 7-segment I Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise a last Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Display type: Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise a last Group 0) Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Material: Plastic Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at least of the composition o | |
| Dimensions: Length: 20,2 cm Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise and selection of the s | LED display |
| Width: 16,3 cm Height: 20,3 cm Weight: 1,03 kg Noise classification: Class 0 (no noise at the second of the seco | |
| Noise classification: Class 0 (no noise at Photobiological safety: Risk Group 0 Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Photobiological safety: Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Mounting bracket Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | at all) |
| Diameter mounting holes: 1 x Ø11mm Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Material: Metal, 2 mm Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Diffusor cover Material: Plastic, 1 mm Color: Frost | |
| Material: Plastic, 1 mm Color: Frost | |
| Color: Frost | |
| | |
| Dimensions: Diameter: Ø 7,7 cr | |
| | cm |
| Remote control | |

| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
|----------------------|---|
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |