

## EUROLITE LED PST-10 QCL Spot

LED pinspot with COB LED and DMX control as well as IR remote control

Art. No.: 51916152

GTIN: 4026397690132



### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 LED 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
- Fixtures available for Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 4°
- With double bracket
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397690132

Weight: 1,20 kg

Length: 0.15 m

Width: 0.15 m

Height: 0.29 m

### Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 12 W

IP classification:	IP20
Protection class:	Protection class II
Power connection:	Fixed power supply cord with Euro plug
Cable construction:	2 x 0.75 mm <sup>2</sup> H05VVH2-F
Cable length:	Approx. 1 m
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 10 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 5; 6; 9
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 1; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	23400 Hz
Beam angle:	4°
Beam angle (1/2 peak):	Spot 4° Frost filter 16°
Beam angle (1/10 peak):	Spot 7° Frost filter 36°
Color temperature:	6500K
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic
Dimensions:	Length: 20.2 cm Width: 16.3 cm Height: 20.3 cm
Weight:	1.03 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	1 x Ø11mm
Material:	Metal, 2 mm
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Material:	Plastic, 1 mm
Dimensions:	Diameter: Ø 7.7 cm
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### Scope of delivery:

1 x spotlight  
1 x remote control  
1 x battery  
1 x frost filter

1 x lamp clamping ring  
1 x user manual