

## EUROLITE LED IP PST-10W 2700K Pinspot

Weather-proof pinspot (IP65) with strong 10 W LED in warm white (WW)

Art. No.: 51916159

GTIN: 4026397617993



**List price: 71.28 €**

incl. 19% VAT.

### Features:

- Compact aluminum housing
- 1 powerful LED 10 W high-power warm white (WW)
- Beam effect
- The device is cooled by passive convection cooling
- Control via plug and play
- With a beam angle of 4°
- With Mounting bracket
- Suitable for outdoor use IP65
- Silent operation
- For application areas such as: Installation; restaurants, bars and hotels; architecture
- Application possibility: Suspended

#### Package contents

- 1 x device, 1 x user manual

### Logistic

EAN / GTIN: 4026397617993

Weight: 0,79 kg

Length: 0.11 m

Width: 0.13 m

Height: 0.17 m

### Technical specifications:

|                    |                                          |
|--------------------|------------------------------------------|
| Power supply:      | 100-240 V AC, 50/60 Hz                   |
| Power consumption: | 10 W                                     |
| IP classification: | IP65                                     |
| Protection class:  | Protection class I                       |
| Power connection:  | Fixed power supply cord with safety plug |
| Cable length:      | Approx. 0,9 m                            |

|                                  |                                                   |
|----------------------------------|---------------------------------------------------|
| Lamp type:                       | LED lamp                                          |
| LED:                             | 1 x 10 W high-power warm white (WW)               |
| Color temperature:               | 2700K                                             |
| Cooling:                         | Passive convection cooling                        |
| Control:                         | Plug and play                                     |
| Beam angle:                      | 4°                                                |
| Beam angle (1/2 peak):           | 4°                                                |
| Beam angle (1/10 peak):          | 6°                                                |
| Illuminance in Lux (lx):         | 1m: 30222 lx, 3m: 4331 lx, 6m: 1130 lx            |
| Luminous flux:                   | 803 lm                                            |
| Housing color:                   | Grey                                              |
| Attachment system:               | Mounting bracket                                  |
| Material:                        | Aluminum casting                                  |
| Dimensions:                      | Width: 10,5 cm<br>Depth: 15 cm<br>Height: 14,7 cm |
| Weight:                          | 790 g                                             |
| Noise classification:            | Class 0 (no noise at all)                         |
| Energy efficiency class (A - G): | F                                                 |
| Mounting bracket                 |                                                   |
| Diameter mounting holes:         | 3 x Ø6mm                                          |
| Material:                        | Aluminum, 2 mm                                    |