

EUROLITE LED PST-40 QCL Spot

LED spotlight with RGBW color mixing, IR remote control and 2 frost filters

Art. No.: 51916170

GTIN: 4026397710625



Features:

- Two additional frost filters provide a soft, homogeneous light
 - 1 LED 40 W 4in1 QCL RGBW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
 - Strobe effect
 - 36 integrated show programs
 - Direct color selection for 15 preset colors
 - The device is cooled by passive convection cooling
 - Control via IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function
 - Fixtures available for Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
 - Flicker-free
 - With a beam angle of 4°
 - With double bracket
 - OLED display
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
 - Silent operation
 - Application possibility: Standing; suspended; on stand
- remote control**
- 24 buttons on the remote control for saving your own settings

Logistic

EAN / GTIN: 4026397710625
Weight: 2,22 kg
Length: 0.19 m
Width: 0.17 m
Height: 0.28 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	36 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	1 x 40 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.8 - 22 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); DMX; sound to light via microphone; master/slave function
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4° Frost filter 20° Frost filter 80°
Beam angle (1/10 peak):	8°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Material:	Plastic; metal
Dimensions:	Length: 12 cm Width: 17 cm Height: 22.5 cm
Weight:	1.98 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø11mm; 3 x Ø2mm
Material:	Metal, 2 mm
Cable construction:	3 x 1.0 mm ² H05VV-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Material:	Plastic, 3 mm
Dimensions:	Width: 12 cm Height: 10.8 cm

Special product: Not designed for household room illumination

Intended use: Show effect lighting

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 2 x frost filter
- 1 x user manual