

EUROLITE LED IP PST-40 QCL Spot

Weather-proof LED spotlight (IP65) with 40 W LED, incl. IR remote control, frost filter & ground stake

Art. No.: 51916175

GTIN: 4026397710724



List price: 296.31 €

incl. 19% VAT.

Features:

- 3 buttons on the remote control for saving your own settings
- Additional frost filter provides a wide, soft and homogeneous light
- 1 powerful LED 40 W 4in1 QCL RGBW (homogenous color mix)
- Frost filter
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone
- Flicker-free
- Easy installation
- With a beam angle of 4°
- With Mounting bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Mobile djs / entertainer; Stage; Leisure facilities/swimming pools/wellness; architecture
- Silent operation
- Mains input and output for power linking up to 8 units
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- With pressure compensation membrane
- Application possibility: Standing; suspended; on stand

Package contents

Logistic

EAN / GTIN: 4026397710724

Weight: 2,52 kg

Length: 0.24 m

Width: 0.20 m

Height: 0.24 m

- 1 x spotlight, 1 x power cord, 1 x stake, 1 x diffusor cover, 1 x remote control, 1 x battery, 1 x screw, 2 x washer, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	36 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug included
Power output:	IP T-Con (F)
Lamp type:	LED lamp
LED:	1 x 40 W 4in1 QCL RGBW (homogenous color mix)
Color temperature:	7400K
Equipment:	Frost filter
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) IP
DMX output:	3-pin XLR (F) IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Setup:	Easy installation
Beam angle:	4°
Beam angle (1/2 peak):	4° Frost filter 20°
Beam angle (1/10 peak):	8°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 11 cm Width: 14,3 cm Height: 19,6 cm
Weight:	2,23 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	3 x 1,0 mm ² H07RN-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 2 x Ø6mm
Material:	Aluminum, 2 mm
Diffusor cover	

Material:	Plastic, 3 mm
Color:	Frost
Dimensions:	Diameter: Ø 10,3 cm
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Stake	
Material:	Plastic
Color:	Black
Dimensions:	Height: 16 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting