

## EUROLITE LED PST-15W MK2 COB RGBW Floor Spot/Wash

Pinspot with 15 W COB LED, beam angles 4°/6°/20° (frost filter)

Art. No.: 51916251

GTIN: 4026397566451



**List price: 189.21 €**

incl. 19% VAT.

### Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 powerful LED 15 W high-power 4in1 QCL RGBW (homogenous color mix)
- 4 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; RDM; Master/slave function
- Flicker-free
- With a beam angle of 4°
- With double bracket
- OLED display
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 2 x diffusor cover, 1 x lamp clamping ring, 1 x user manual

### Logistic

EAN / GTIN: 4026397566451

Weight: 1,57 kg

Length: 0.29 m

Width: 0.19 m

Height: 0.14 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	17 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC (M) power supply cord with safety plug (provided)
Power output:	1 x IEC (F)
Lamp type:	LED lamp
LED:	1 x 15 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; RDM; Master/slave function
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4° 6° 20°
Beam angle (1/10 peak):	7° 11° 35°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Material:	Aluminum casting
Dimensions:	Width: 13,5 cm Depth: 19 cm Height: 22 cm
Weight:	1,42 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,3 m
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm; 2 x Ø3mm
Material:	Aluminum, 3 mm
Diffusor cover	

Color:	Frost
Dimensions:	Width: 2 mm Diameter: Ø 8,2 cm
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Lamp clamping ring	
Material:	Metal, 2 mm
Color:	Black
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting