

EUROLITE LED RETRO 6 Spot ABL

Warm white blinder with additional colored LEDs for atmospheric lighting

Art. No.: 51916605

GTIN: 4026397755633



List price: 296.31 €

incl. 19% VAT.

Description:

The "Retro" in the name of this fixture is no coincidence: six powerful LED strips extend from the center outward like the spokes of a wheel, producing a very warm, almost orange-toned white light in a classic retro style.

Each strip is equipped with a 60 W LED and can be controlled individually. Between the strips are reflective sections illuminated by a total of 108 RGB LEDs. These are divided into 12 segments and can be controlled accordingly.

A variety of DMX modes are available. In the most advanced mode, all elements can be controlled individually, while reduced modes still offer extensive possibilities even with smaller DMX controllers.

The series also includes a matching bar that delivers the same effects in a different form factor.

Features:

- 6 LEDs 60 W COB (chip-on-board) amber (A)
 LEDs controlled separately
- 108 LEDs 0.1 W SMD 5050 3in1 R/G/B (homogenous color mix)
12 segments controlled separately
- Dimmer electronic
- Blinder effect
- 3 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; sound to light; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 120°

Logistic

EAN / GTIN: 4026397755633

Weight: 5,70 kg

Length: 0.43 m

Width: 0.17 m

Height: 0.46 m

- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; theater; restaurants, bars and hotels; rental
- Very quiet working noise
- Application possibility: Standing; suspended
- Fixtures available for Light Captain

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	200 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.5 mm ² H05VV-F
Power output:	P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	6 x 60 W COB (chip-on-board) amber (A) 108 x 0.1 W SMD 5050 3in1 R/G/B (homogenous color mix)
Flash rate:	0.8 - 20 Hz
DMX channels:	6; 10; 12; 16; 49
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	2 x temperature-controlled fan
Control:	DMX; stand-alone; sound to light; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	4000 Hz
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	1800K
Lamp life:	30000 h
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Use of brands:	Built with SEETRONIC connector
Material:	Metal
Dimensions:	Width: 36 cm Depth: 11 cm Height: 37.5 cm

Weight:	5.00 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual