

EUROLITE LED D-30 Hybrid Beam Effect

DMX lighting effect with RGBWAP derby, white strobe LEDs, and IR remote control

Art. No.: 51918310 GTIN: 4026397551419











List price: 213.01 €

incl. 19% VAT.

Description:

The LED D-30 Beam Effect by Eurolite comes equipped with six 3-watt LEDs in the colors red, green, blue, amber and pink as well as 36 cold white SMD LEDs creating dynamic strobe and derby effects.

The LED D-30 works with 3 preset programs. In the automatic mode, the preset light programs are played fully automatically without any further adjustments on your part. Alternatively, you can choose the sound-controlled mode via the built-in microphone with adjustable sensitivity. In this mode, the multi-color beams change direction with each bass beat.

You can also operate multiple devices in sync using the master/slave mode.

Apart from the preset programs, the LED D-30 can also be controlled via 4 or 13 DMX channels. For the addressing and settings you can either use the 4-digit LED display and operating buttons on the rear of the device or the supplied IR remote control.

Features:

- Precision lenses fill the room with countless rotating beams
- 36 powerful LEDs SMD 5050 cold white (CW)
- 6 powerful LEDs 3 W high-power 6in1 HCL RGBWAP
- Multi beam effect; Strobe effect
- 3 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; Sound to light via Microphone; IR remote control
- With a beam angle of 120°
- With Mounting bracket
- Monochrome 4 digit 7-segment LED display
- Dimmer electronic; Rotation speed stepless
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain

Logistic

EAN / GTIN: 4026397551419

Weight: 2,90 kg Length: 0.34 m Width: 0.34 m Heigth: 0.22 m

- For application areas such as: Clubs/dancing school; Party room; mobile djs / entertainer; small rental
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Technical specifications:

| recimical specifications. | |
|---------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 36 W |
| IP classification: | IP20 |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED: | 36 x SMD 5050 cold white (CW) 6 x 3 W high-power 6in1 HCL RGBWAP |
| DMX channels: | 4; 13 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; Sound to light via Microphone; IR remote control |
| Preprogrammed in: | Light´J; LED PC-Control 512; Light Captain |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | Monochrome 4 digit 7-segment LED display |
| Material: | Metal |
| Dimensions: | Width: 28,0 cm Depth: 29,0 cm Height: 19,0 cm |
| Weight: | 2,40 kg |
| Power cord | |
| Cable construction: | 3 x 0,75 mm² H05VV-F |
| Cable length: | 1,2 m |
| Color: | Black |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| | |