

EUROLITE LED WF-100 Water Effect

LED projection effect for water reflections with color wheel & DMX

Art. No.: 51918547 GTIN: 4026397737646











List price: 355.81 €

incl. 19% VAT.

Features:

- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
- Animation wheel; focus manual
- Dimmer; color change adjustable; Rotation speed stepless
- Water effect; strobe effect
- Color wheel with 5 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- 8 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone
- Preprogrammed in Light Captain; Colorchief
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 45°
- With mounting bracket
- 4 digit 7-segment LED display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397737646

Weight: 5,50 kg Length: 0.41 m Width: 0.33 m Heigth: 0.22 m

Technical specifications:

Power consumption: 140 W IP classification: IP20 Protection class: Protection class I Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug Cable construction: 3 x 1,0 mm² H05VV-F Cable length: 1,45 m Power output: P-Con (gray), mounting version Power output: P-Con (gray), mounting version Fuse: 5 x 20 mm, T 2 A fuse replaceable Lamp type: LED lamp LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by vireless solution (optional); Stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket USB port: Type A Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x 212mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: Mot designed for household room illumination Special product: Not designed for household room illumination	Power supply:	100-240 V AC, 50/60 Hz	
Protection class: Protection class I Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug Cable construction: 3 x 1,0 mm² H05VV-F Cable length: 1,45 m Power output: P-Con (gray), mounting version Fuse: 5 x 20 mm, T 2 A fuse replaceable Lamp type: LED lamp LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Color generation: Color generation: DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (M) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); w-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Øl2mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Power consumption:	140 W	
Power connection: Mains input via P-Con (blue), mounting version power supply cord with safety plug Cable construction: 3 x 1,0 mm² H05VV-F Cable length: 1,45 m Power output: P-Con (gray), mounting version Fuse: 5 x 20 mm, T 2 A fuse replaceable Lamp type: LED lamp LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); vB-DMX by wireless solution (optional); CRMX by uireless solution (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket 46° Housing color: Black Attachment system: Mounting bracket 46° Housing color: Black Attachment system: Mounting bracket 46° Housing color: Black Attachment system: Mounting bracket 47° A x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	IP classification:	IP20	
Cable construction: 3 x 1,0 mm² H05VV-F Cable length: 1,45 m Power output: P-Con (gray), mounting version Fuse: 5 x 20 mm, T 2 A fuse replaceable Lamp type: LED lamp LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Color generation: Color generation: MX channels: 5 MX channels: 5 MX channels: 5 MX output: 3-pin XLR (M) mounting version MX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Type A Transport aid: A x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Protection class:	Protection class I	
Cable length: 1,45 m Power output: P-Con (gray), mounting version Fuse: 5 x 20 mm, T 2 A fuse replaceable Lamp type: LED lamp LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 19,5 cm Weight: 19,5 cm Weight: 19,5 cm Legal specifications	Power connection:		
Power output: Prese: S x 20 mm, T 2 A fuse replaceable Lamp type: LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); W-DMX by wireless solution (optional); Stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classifications	Cable construction: 3 x 1,0 mm² H05VV-F		
Fuse: 5 x 20 mm, T 2 A fuse replaceable Lamp type: LED tamp LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32.0 cm Depth: 23.5 cm Height: 19.5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Cable length:	1,45 m	
Lemp type: LED lamp LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); CRMX by wireless solution (optional); and alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket UsB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Power output:	P-Con (gray), mounting version	
LED type: 1 x 100 W COB (chip-on-board) cold white (CW) Flash rate: 0 - 30 Hz Equipment: Animation wheel; focus manual Color generation: Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Fuse:	5 x 20 mm, T 2 A fuse replaceable	
Flash rate: Equipment: Animation wheel; focus manual Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fall mode: Hold; blackout Beam angle: 45° Housing color: Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display Type A Transport aid: 7 ype A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Lamp type:	LED lamp	
Equipment: Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Metail Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	LED type:	1 x 100 W COB (chip-on-board) cold white (CW)	
Color generation: Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Flash rate:	0 - 30 Hz	
Half colors selectable, Rainbow effect with adjustable speed in both directions DMX channels: 5 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Equipment:	Animation wheel; focus manual	
DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Color generation:	Half colors selectable, Rainbow effect with	
DMX output: 3-pin XLR (F) mounting version Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	DMX channels:	5	
Cooling: 3 x temperature-controlled fan Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	DMX input:	3-pin XLR (M) mounting version	
Control: QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); Stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	DMX output:	3-pin XLR (F) mounting version	
wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone Preprogrammed in: Light Captain; Colorchief Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used	Cooling:	3 x temperature-controlled fan	
Projection: Flicker-free DMX fail mode: Hold; blackout Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DN master/slave function; sound to light via		
DMX fail mode: Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	Preprogrammed in:	Light Captain; Colorchief	
Beam angle: 45° Housing color: Black Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm	Projection:	<u> </u>	
Housing color: Attachment system: Mounting bracket Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	DMX fail mode:	Hold; blackout	
Attachment system: Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	Beam angle: 45°		
Display type: 4 digit 7-segment LED display USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	Housing color:	Black	
USB port: Type A Transport aid: 4 x rubber feet Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications			
Transport aid: Diameter mounting holes: 3 x Ø12mm Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	Display type:	4 digit 7-segment LED display	
Diameter mounting holes: Metal Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	USB port:	SB port: Type A	
Material: Metal Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	ransport aid: 4 x rubber feet		
Dimensions: Width: 32,0 cm Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	Diameter mounting holes:	3 x Ø12mm	
Depth: 23,5 cm Height: 19,5 cm Weight: 4,75 kg Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	Material:	Metal	
Noise classification: Class 2 (slight noise) depending on mode used Legal specifications	Dimensions:	Depth: 23,5 cm	
Legal specifications	Weight:	4,75 kg	
	Noise classification:	Class 2 (slight noise) depending on mode used	
Special product: Not designed for household room illumination	Legal specifications		
	Not designed for household room illumination		

Intended use:	Show effect lighting