

## EUROLITE LED WF-100 Water Effect

LED projection effect for water reflections with color wheel & DMX

Art. No.: 51918547

GTIN: 4026397737646



### Features:

- 1 LED 100 W COB (chip-on-board) cold white (CW)
- Animation wheel; focus manual
- Dimmer; color change adjustable; Rotation speed stepless
- Water effect; strobe effect
- Color wheel with 5 dichroic filters plus open half colors selectable, Rainbow effect with adjustable speed in both directions
- 8 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone
- Fixtures available for Light Captain; Colorchief
- Flicker-free
- DMX fail mode (hold; blackout)
- With a beam angle of 45°
- With mounting bracket
- 4 digit 7-segment LED display
- 4 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; decoration
- Application possibility: Suspended; on stand

### Logistic

EAN / GTIN: 4026397737646

Weight: 5,50 kg

Length: 0.41 m

Width: 0.33 m

Height: 0.22 m

## Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	140 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Cable construction:	3 x 1.0 mm <sup>2</sup> H05VV-F
Cable length:	1.45 m
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) cold white (CW)
Flash rate:	0.4 - 24 Hz
Equipment:	Animation wheel; focus manual
Color generation:	Color wheel with 5 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
DMX channels:	5
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	3 x temperature-controlled fan
Control:	QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); stand-alone; DMX; master/slave function; sound to light via microphone
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
PWM frequency:	11700 Hz
DMX fail mode:	Hold; blackout
Beam angle:	45°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
USB port:	Type A
Transport aid:	4 x rubber feet
Diameter mounting holes:	3 x Ø12mm
Material:	Metal
Dimensions:	Width: 32.0 cm Depth: 23.5 cm Height: 19.5 cm
Weight:	4.75 kg
Noise classification:	Class 2 (slight noise) depending on mode used
Special product:	Not designed for household room illumination

Intended use:

Show effect lighting

---

**Scope of delivery:**

---

- 1 x light effect
- 1 x user manual
- 1 x power cord