

# **EUROLITE LED DMF-4 Hybrid Flower Effect**

Spotlight with flower- and stroboscope effect, incl. IR remote control

**Art. No.: 51918563** GTIN: 4026397695052











List price: 95.08 €

incl. 19% VAT.

# Features:

- 2 strips with white LEDs provide fast, dynamic strobe sffects
- 70 powerful LEDs 5 mm R/G/B
- 12 powerful LEDs SMD 5050 cold white (CW)
- Flower effect; Strobe effect
- 4 integrated show programs
- Direct color selection for 8 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain
- With a beam angle of 37°
- With Mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; Party room; small rental
- Very quiet working noise
- Application possibility: Suspended; on stand

#### Package contents

- 1 x device, 1 x power cord, 1 x user manual, 1 x remote control, 1 x battery

### **Technical specifications:**

| Power supply:      | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 10 W                   |

## Logistic

EAN / GTIN: 4026397695052

Weight: 1,45 kg Length: 0.23 m Width: 0.22 m Heigth: 0.13 m

| IP classification:     | IP20   |
|------------------------|--|
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)   |
| Fuse:                  | T 0,5 A Fuse replaceable   |
| LED:                   | 70 x 5 mm R/G/B  |
|                        | 12 x SMD 5050 cold white (CW)  |
| DMX channels:          | 7  |
| DMX input:             | 3-pin XLR (M) mounting version   |
| DMX output:            | 3-pin XLR (F) mounting version   |
| Cooling:               | Passive convection cooling   |
| Control:               | Stand-alone; IR remote control; DMX; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in:      | Light Captain  |
| Beam angle:            | 37°  |
| Beam angle (1/2 peak): | 37°  |
| Housing color:         | Black  |
| Attachment system:     | Mounting bracket   |
| Display type:          | 4 digit 7-segment LED display  |
| Dimensions:            | Length: 19,4 cm  |
|                        | Width: 20,2 cm   |
|                        | Height: 12,3 cm  |
| Weight:                | 1,30 kg  |
| Noise classification:  | Class 1 (very slight noise, suitable for noise-<br>sensitive environments)   |
| Remote control         |  |
| Battery:               | 1 x Button cell 3.0 V CR2025 lithium manganese built-in  |
| Legal specifications   |  |
| Special product:       | Not designed for household room illumination   |
| Intended use:          | Show effect lighting   |
|                        |  |