

EUROLITE LED SCY-500 CW Beam Effect

LED effect light with cold white COB LEDs and stroboscope

Art. No.: 51918673

GTIN: 4026397692266



List price: 415.31 €

incl. 19% VAT.

Features:

- 5 powerful LEDs 15 W high-power cold white (CW) LEDs controlled separately
- Fan effect
- 3 integrated show programs
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light Captain
- With a beam angle of 4°
- With Mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; Rental
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x user manual, 1 x remote control, 1 x battery, 1 x power cord

Logistic

EAN / GTIN: 4026397692266

Weight: 3,90 kg

Length: 0.45 m

Width: 0.29 m

Height: 0.17 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 75 W

IP classification: IP20

Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 1 A Fuse replaceable
LED:	5 x 15 W high-power cold white (CW)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 5; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain
Beam angle:	4°
Beam angle (1/2 peak):	Beam 4° Multi beam effect 90°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 39 cm Depth: 25 cm Height: 18 cm
Weight:	3,33 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting