eurolite®

EUROLITE LED Pixel Pole 100cm

LED bar for pixel mapping applications







And Address in case

The article is no longer in our assortment.

Features:

- LED bar with 16 or 32 pixels for video and pixel mapping applications via Art-Net
- Signal distribution via UTP cable
- Easily create animations with MADRIX or any other control software supporting Art-Net
- 32 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; Dimmer electronic
- Strobe effect
- 30 integrated show programs
- The device is cooled by passive convection cooling
- Control via accessory; master/slave function
- With a beam angle of 180°
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; stage

Technical specifications:

Power supply:	24V DC
Power consumption:	4 W
IP classification:	IP20
Power connection:	Mains input via RJ-45 (F) mounting version
LED type:	32 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Cooling:	Passive convection cooling

Logistic

EAN / GTIN: 4026397644159 Weight: 0,20 kg Length: 1.00 m Width: 0.03 m Heigth: 0.03 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Control:	Accessory; master/slave function
Beam angle:	180°
Beam angle (1/2 peak):	180°
Image:	Pixel pitch 30 mm
Housing color:	Clear
Connections:	Signal via 2 x RJ-45 (F) mounting version
Dimensions:	Length: 100 cm
	Depth: 3,2 cm
	Height: 3,2 cm
Weight:	0,20 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting