

EUROLITE LED CBB-4 COB RGB Bar

LED light effect bar with RGB color mixing, incl. IR remote control

Art. No.: 51930278

GTIN: 4026397616033



List price: 236.81 €

incl. 19% VAT.

Features:

- 4 powerful LEDs 23 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - Strobe effect
 - Integrated show programs
 - Direct color selection for 19 preset colors
 - The device is cooled by low-noise cooling fan
 - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
 - Flicker-free
 - With a beam angle of 39°
 - With Mounting bracket
 - 4 digit 7-segment LED display
 - Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
 - Mains input and output for power linking up to 8 units
 - For application areas such as: Clubs/dancing school; Stage; theater; mobile djs / entertainer
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397616033

Weight: 4,36 kg

Length: 0.51 m

Width: 0.15 m

Height: 0.26 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	70 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	T 1 A Fuse replaceable
Lamp type:	LED lamp
LED:	4 x 23 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5; 12; 15; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	1 x low-noise cooling fan
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	39°
Beam angle (1/2 peak):	39°
Beam angle (1/10 peak):	70°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 46 cm Depth: 16 cm Height: 16 cm
Weight:	3,97 kg
Noise classification:	Class 2 (slight noise)
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,1 m
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 4 x Ø8mm
Material:	Metal, 2,5 mm
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting