

EUROLITE LED PIX-144/72 RGB/CW Bar

LED light bar with wide beam SMD LEDs (RGB/CW) and pixel control

Art. No.: 51930353

GTIN: 4026397709650



List price: 177.31 €

incl. 19% VAT.

Features:

- 144 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
 segments controlled separately
- 72 powerful LEDs SMD 5730 cold white (CW)
- 16 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; Master/slave function; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 120°
- With Mounting bracket
- 4 digit 7-segment LED display
- Color change adjustable; Dimmer electronic; color blend stepless; running light; background color adjustable
- Strobe effect
- Preprogrammed in Light´J; Light Captain
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; Wall mounting

Package contents

- 1 x bar, 1 x user manual, 1 x power cord, 2 x mounting bracket, 2 x screw, 2 x washer

Logistic

EAN / GTIN: 4026397709650

Weight: 1,94 kg

Length: 1.03 m

Width: 0.12 m

Heigh: 0.11 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
LED:	144 x SMD 5050 3in1 TCL RGB (homogenous color mix) 72 x SMD 5730 cold white (CW)
Flash rate:	10 Hz
DMX channels:	6; 16; 84
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; Master/slave function; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light´J; Light Captain
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	2x Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 1,085 m Depth: 6,5 cm Height: 9,0 cm
Weight:	1,63 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting