

EUROLITE LED BAR-3 HCL Bar

Compact (26 cm) bar with 3 x 12 W 6in1 LED and RGBWA+UV color mixing

Art. No.: 51930395

GTIN: 4026397617177



List price: 112.93 €

incl. 19% VAT.

Features:

- 3 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in EASY SHOW 3; EASY SHOW 2; Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- For application areas such as: Clubs/dancing school; Party room; restaurants, bars and hotels; small rental
- Silent operation
- Application possibility: Suspended; Wall mounting

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397617177

Weight: 1,28 kg

Length: 0.28 m

Width: 0.12 m

Height: 0.17 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption:	12 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 0,5 A Fuse replaceable
Lamp type:	LED lamp
LED:	3 x 12 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 3; 4; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function
Preprogrammed in:	EASY SHOW 3; EASY SHOW 2; Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Beam angle (1/10 peak):	40°
Wavelength:	Ultra violet (UV) 400 nm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal; Plastic hard
Dimensions:	Length: 26,5 cm Depth: 8,7 cm Height: 12,9 cm
Weight:	1,13 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Mounting bracket	
Diameter mounting holes:	1 x Ø11mm; 4 x Ø8mm; 2 x Ø5mm
Material:	Metal, 2 mm
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting