

EUROLITE LED BAR-6 QCL RGBA Bar

LED bar (59cm) with 6 x 4 watt 4in1 QCL RGBA LED

Art. No.: 51930397 GTIN: 4026397603538



List price: 112.93 €

incl. 19% VAT.

Features:

- 6 powerful LEDs 4 W high-power 4in1 QCL RGBA (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Preprogrammed in LED PC-Control 512; Light'J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
- Silent operation
- Application possibility: Suspended; wall mounting

Package contents

 1 x light effect, 2 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W

Logistic

EAN / GTIN: 4026397603538

Weight: 1,95 kg Length: 0.56 m Width: 0.12 m Heigth: 0.12 m

IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 4 W high-power 4in1 QCL RGBA (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	LED PC-Control 512; Light 'J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum; metal
Dimensions:	Length: 59 cm
	Depth: 6,5 cm Height: 10 cm
Weight:	1,75 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	Then Group C
Diameter mounting holes:	1 x Ø20mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,2 m
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting