

EUROLITE LED PIX-7 Hybrid SCL Bar

Light effect bar with RGBA/CW/WW+UV LEDs and pixel control

Art. No.: 51930407

GTIN: 4026397643664



Features:

- Each 7in1 LED can be controlled individually
- Mains input and output for power linking up to 8 units
- Strobe effect; UV effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; Light Captain; Light´J
- Flicker-free
- With a beam angle of 18°
- With mounting bracket
- Silent operation
- light effect**
- 6 LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- strobes**
- 72 LEDs 0.5 W SMD 5050 3in1 TCL RGB (homogenous color mix)

Logistic

EAN / GTIN: 4026397643664

Weight: 4,45 kg

Length: 0.54 m

Width: 0.16 m

Height: 0.23 m

Technical specifications:

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 50 W

IP classification: IP20

Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
Flash rate:	0 - 20 Hz
DMX channels:	3; 7; 9; 22; 43
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; IR remote control; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	18°
Beam angle (1/2 peak):	18°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 50 cm Depth: 10 cm Height: 14.9 cm
Weight:	3.95 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
LED type:	72 x 0.5 W SMD 5050 3in1 TCL RGB (homogenous color mix)
LED type:	6 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

Scope of delivery:

1 x remote control