

EUROLITE Disco Strobe 25

Simple, compact strobe

Art. No.: 5220060P

GTIN: 4026397617207











List price: 16.07 €

incl. 19% VAT.

Description:

This basic strobe effect is perfectly suited for your private party room.

Thanks to the mounting bracket, it can easily be mounted to a wall or ceiling.

The flash frequency can be adjusted from 1-10 flashes per second using the rotary control.

Features:

- Small strobe effect with high output
- High-quality strobe flash tube
- Flash rate adjustable
- Lightweight plastic housing
- Strobe effect
- Control via stand-alone
- With a beam angle of 60°
- Very high color rendering index (CRI)
- With mounting bracket
- For application areas such as: Party room; decoration; advertisement/Shop window
- Very quiet working noise
- Application possibility: Suspended

Package contents

- 1 x strobes, 1 x user manual

Technical specifications:

Power supply: 230 V AC, 50 Hz

Logistic

EAN / GTIN: 4026397617207

Weight: 0,24 kg Length: 0.17 m Width: 0.10 m Heigth: 0.06 m

Protection class: Protection class II Power connection: Fixed power supply cord with Euro plug Approx. 0,9 m Flash rate: 0 - 10 Hz Control: Stand-alone Beam angle: 60° Beam angle (1/2 peak): Color of light: Cold white CW >5000 K Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Power consumption:	20 W
Power connection: Fixed power supply cord with Euro plug Cable length: Approx. 0,9 m Flash rate: 0 - 10 Hz Control: Stand-alone Beam angle: 60° Beam angle (1/2 peak): Color of light: Cold white CW >5000 K Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	IP classification:	IP20
Cable length: Approx. 0,9 m Flash rate: 0 - 10 Hz Control: Stand-alone Beam angle: 60° Beam angle (1/2 peak): Color of light: Cold white CW >5000 K Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Protection class:	Protection class II
Flash rate: 0 - 10 Hz Control: Stand-alone Beam angle: 60° Beam angle (1/2 peak): 60° Color of light: Cold white CW >5000 K Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Power connection:	Fixed power supply cord with Euro plug
Control: Stand-alone Beam angle: 60° Beam angle (1/2 peak): 60° Color of light: Cold white CW >5000 K Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Cable length:	Approx. 0,9 m
Beam angle: 60° Beam angle (1/2 peak): 60° Color of light: Cold white CW >5000 K Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Flash rate:	0 - 10 Hz
Beam angle (1/2 peak): Color of light: Cold white CW >5000 K Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Control:	Stand-alone
Color of light: Color rendering index (CRI): 98 Ra Attachment system: Mounting bracket Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Beam angle:	60°
Color rendering index (CRI): Attachment system: Mounting bracket Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: O,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Beam angle (1/2 peak):	60°
Attachment system: Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: O,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Color of light:	Cold white CW >5000 K
Dimensions: Length: 13,7 cm Width: 9,5 cm Height: 8,8 cm Weight: O,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Color rendering index (CRI):	98 Ra
Width: 9,5 cm Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Attachment system:	Mounting bracket
Height: 8,8 cm Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Dimensions:	Length: 13,7 cm
Weight: 0,20 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm		Width: 9,5 cm
Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Illuminant Lamp type: Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm		Height: 8,8 cm
Sensitive environments) Illuminant Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Weight:	0,20 kg
Lamp type: Strobe lamp Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Noise classification:	
Construction: Tube Mounting bracket Diameter mounting holes: 1 x Ø5mm	Illuminant	
Mounting bracket Diameter mounting holes: 1 x Ø5mm	Lamp type:	Strobe lamp
Diameter mounting holes: 1 x Ø5mm	Construction:	Tube
	Mounting bracket	
Material: Plastic, 3 mm	Diameter mounting holes:	1 x Ø5mm
	Material:	Plastic, 3 mm