

## EUROLITE LED Strobe COB PRO 8x20W DMX

LED strobe with 8 x 20 W COB LED and adjustable flash frequency

Art. No.: 52200870

GTIN: 4026397544565



**List price: 236.81 €**

incl. 19% VAT.

### Description:

This LED strobe is equipped with 8 x 20-watt COB LEDs and combines strobe, chase and blinder effects. It lets you create both dynamic stage shows and the more low-key effects in between with a single fixture.

You can choose from three different operation modes: master-slave, stand-alone and DMX mode (5 DMX channels). The integrated microphone makes for great light effects to the rhythm of the music.

The fixture has 3-pin DMX connectors as well as an IEC input to connect it to the mains.

### Features:

- Elaborate reflector system
- 8 powerful LEDs 20 W COB (chip-on-board) cold white (CW)
- Dimmer electronic; effect speed adjustable
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- For application areas such as: Clubs/dancing school; mobile djs / entertainer; Stage
- Very quiet working noise
- Application possibility: Suspended; on stand

#### Package contents

- 1 x device, 1 x power cord, 1 x user manual

### Logistic

EAN / GTIN: 4026397544565

Weight: 2,65 kg

Length: 0.39 m

Width: 0.22 m

Height: 0.18 m

## Technical specifications:

|                                  |                                                                                                  |
|----------------------------------|--------------------------------------------------------------------------------------------------|
| Power supply:                    | 100-240 V AC, 50/60 Hz                                                                           |
| Power consumption:               | 95 W                                                                                             |
| IP classification:               | IP20                                                                                             |
| Protection class:                | Protection class I                                                                               |
| Power connection:                | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Fuse:                            | 5 x 20 mm, F 3 A Fuse replaceable                                                                |
| Lamp type:                       | LED lamp                                                                                         |
| LED:                             | 8 x 20 W COB (chip-on-board) cold white (CW)                                                     |
| Color temperature:               | 6500K                                                                                            |
| DMX channels:                    | 5                                                                                                |
| DMX input:                       | 1 x 3-pin XLR (M) mounting version                                                               |
| DMX output:                      | 1 x 3-pin XLR (F) mounting version                                                               |
| Cooling:                         | 1 x cooling fan                                                                                  |
| Control:                         | Stand-alone; DMX; Sound to light via Microphone                                                  |
| Preprogrammed in:                | Light J; LED PC-Control 512; Light Captain                                                       |
| Luminous flux:                   | 4800 lm                                                                                          |
| Housing color:                   | Black                                                                                            |
| Attachment system:               | Mounting bracket                                                                                 |
| Display type:                    | 4 digit 7-segment LED display                                                                    |
| Material:                        | Metal                                                                                            |
| Dimensions:                      | Width: 34,5 cm<br>Depth: 11 cm<br>Height: 18 cm                                                  |
| Weight:                          | 2,35 kg                                                                                          |
| Noise classification:            | Class 1 (very slight noise, suitable for noise-sensitive environments)                           |
| Energy efficiency class (A - G): | G                                                                                                |
| Power cord                       |                                                                                                  |
| Cable construction:              | 3 x 0,75 mm <sup>2</sup> H05VV-F                                                                 |
| Cable length:                    | Approx. 1,4 m                                                                                    |
| Mounting bracket                 |                                                                                                  |
| Diameter mounting holes:         | 3 x Ø11mm                                                                                        |
| Material:                        | Metal, 1,5 mm                                                                                    |