

EUROLITE LED IP PIX Strobe RGB CW+WW

Outdoor spotlight (IP65) for stroboscope, ambient and animation effects

Art. No.: 52200940

GTIN: 4026397727661



Features:

- Compact and bright
- Show programs for white and colored LEDs on separate DMX channels
- 240 LEDs 0.5 W SMD 5050 3in1 TCL RGB
8 segments controlled separately
- 40 LEDs 1 W SMD 3030 2in1 BCL CW/WW
4 segments controlled separately
- Dimmer electronic; color blend stepless; program speed adjustable; program selection adjustable; color animations with two adjustable colors
- Ambient effect; strobe effect; wash effect
- 20 integrated show programs
- The device is cooled by passive convection cooling
- Control via stand-alone; sound to light via microphone; master/slave function; DMX
- Fixtures available for Colorchief; Light Captain; GDTF (GrandMA3)
- Flicker-free
- With a beam angle of 120°
- Variable color temperature 3200 K - 6600 K
- With mounting bracket
- OLED display
- Mains input and output for power linking up to 8 units
- Built with SEETRONIC connector
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; architecture; restaurants, bars and hotels; theater; rental
- Silent operation
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397727661

Weight: 3,68 kg

Length: 0.41 m

Width: 0.20 m

Height: 0.16 m

Technical specifications:

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 135 W |
| IP classification: | IP65 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IP T-Con (M) mounting version power supply cord with safety plug |
| Power output: | IP T-Con (F) mounting version |
| Fuse: | T 5 A fuse fix in power supply |
| Lamp type: | LED lamp |
| LED type: | 240 x 0.5 W SMD 5050 3in1 TCL RGB 40 x 1 W SMD 3030 2in1 BCL CW/WW |
| Flash rate: | 1 - 25 Hz |
| DMX channels: | 6; 10; 18; 24; 25; 32 |
| DMX input: | 1 x 3-pin XLR (M) mounting version IP |
| DMX output: | 1 x 3-pin XLR (F) mounting version IP |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; sound to light via microphone; master/slave function; DMX |
| Fixtures available for: | Colorchief; Colorchief; Light Captain; GDTF (GrandMA3) |
| Projection: | Flicker-free |
| PWM frequency: | 4000 Hz |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Color temperature: | 3200K - 6600K adjustable |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | OLED display |
| Use of brands: | Built with SEETRONIC connector |
| Dimensions: | Length: 38 cm Depth: 11 cm Height: 14.5 cm |
| Weight: | 3.30 kg |
| Noise classification: | Class 0 (no noise at all) |
| Diameter mounting holes: | 3 x Ø13mm |
| Material: | Metal, 3 mm |
| Cable construction: | 3 x 1.5 mm ² H07RN-F |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

Scope of delivery:

1 x device
1 x user manual
1 x power cord