

EUROLITE LED Mega Strobe 768 Bar

Strobe bar with colored and white pixel LEDs and switchable frost

Art. No.: 52200950 GTIN: 4026397707526



List price: 712.81 €

incl. 19% VAT.

Features:

- 384 powerful LEDs SMD 3528 cold white (CW)
- 384 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless; dimmer curves adjustable; frost filter electronic
- Strobe effect
- 37 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; Master/slave function
- Flicker-free
- With panning and tilting mounting bracket for ceiling or wall installation in most varying angles
- LCD display
- Preprogrammed in Light Captain
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; mobile djs / entertainer; Rental
- Very quiet working noise
- Application possibility: Suspended; standing

Package contents

- 1 x light effect, 1 x power cord, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	350 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397707526

Weight: 7,40 kg Length: 1.06 m Width: 0.14 m Heigth: 0.20 m

LED: 384 x SMD 3528 cold white (CW) 384 x SMD 5050 3in1 TCL RGB (homogenous color mix) DMX channels: 7; 18; 21; 113; 125; 257; 269 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: DMX; stand-alone; Master/slave function Preprogrammed in: Light Captain Projection: Flicker-free Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments)	Protection class:	Protection class I
384 x SMD 5050 3in1 TCL RGB (homogenous color mix) DMX channels: 7; 18; 21; 113; 125; 257; 269 DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: DMX; stand-alone; Master/slave function Preprogrammed in: Light Captain Projection: Flicker-free Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Fuse:	T 4 A Fuse replaceable
DMX input: 3-pin XLR (M) mounting version DMX output: 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: DMX; stand-alone; Master/slave function Preprogrammed in: Light Captain Projection: Flicker-free Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	LED:	384 x SMD 5050 3in1 TCL RGB (homogenous
DMX output: 3-pin XLR (F) mounting version Cooling: Temperature-controlled fan Control: DMX; stand-alone; Master/slave function Preprogrammed in: Light Captain Projection: Flicker-free Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	DMX channels:	7; 18; 21; 113; 125; 257; 269
Cooling: Temperature-controlled fan Control: DMX; stand-alone; Master/slave function Preprogrammed in: Light Captain Projection: Flicker-free Beam angle (1/2 peak): Strobe effect 65°	DMX input:	3-pin XLR (M) mounting version
Control: DMX; stand-alone; Master/slave function Preprogrammed in: Light Captain Projection: Flicker-free Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	DMX output:	3-pin XLR (F) mounting version
Preprogrammed in: Light Captain Projection: Flicker-free Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Cooling:	Temperature-controlled fan
Projection: Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Control:	DMX; stand-alone; Master/slave function
Beam angle (1/2 peak): Strobe effect 65° Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Preprogrammed in:	Light Captain
Ambient light 50° Attachment system: Panning and tilting mounting bracket for ceiling or wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Projection:	Flicker-free
wall installation in most varying angles Display type: LCD display Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Beam angle (1/2 peak):	
Dimensions: Length: 1 m Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Attachment system:	
Depth: 13,5 cm Height: 8,5 cm Weight: 6,55 kg Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Display type:	LCD display
Noise classification: Class 1 (very slight noise, suitable for noise-sensitive environments) Legal specifications Special product: Not designed for household room illumination	Dimensions:	Depth: 13,5 cm
Legal specifications Special product: Not designed for household room illumination	Weight:	6,55 kg
Special product: Not designed for household room illumination	Noise classification:	
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting