

EUROLITE LED SLS-98 Strobe SMD

Compact strobe with 98 SMD LEDs & DMX, each ring individually controllable

Art. No.: 52201092

GTIN: 4026397613346



List price: 117.81 €

incl. 19% VAT.

Description:

This compact strobe light in a slim-line design is equipped with a total of 98 flicker-free SMD 5030 LEDs and offers you both strobe and blinder effects. The flash frequency is 1-20 flashes per second. The strobe can be operated in stand-alone mode, with a DMX controller or by sound control via the built-in microphone. Delivery includes an IR remote control for convenient operation from a distance.

In DMX mode, the 5 ring-shaped LED segments can be controlled individually or in groups. You can choose from two DMX modes with 4 or 9 channels respectively. The fixture has 3-pin DMX connectors as well as an IEC input to connect it to the mains and a feed-through output for daisy-chaining up to 8 units.

Features:

- Flat version requires minimal space when mounting
- 98 powerful LEDs SMD 5730 cold white (CW) (homogenous color mix)
5 segments controlled separately
- Dimmer electronic
- Strobe effect; Blinder effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- Preprogrammed in LED PC-Control 512; Light Captain
- Flicker-free
- With double bracket
- Mains input and output for power linking up to 8 units

Logistic

EAN / GTIN: 4026397613346

Weight: 1,45 kg

Length: 0.27 m

Width: 0.23 m

Height: 0.16 m

- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; small rental
- Very quiet working noise
- Application possibility: Standing; suspended

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	98 x SMD 5730 cold white (CW) (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	4; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone; IR remote control
Preprogrammed in:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
Attachment system:	Double bracket
Dimensions:	Width: 21,5 cm Depth: 12 cm Height: 24,5 cm
Weight:	1,20 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting