

EUROLITE Safety Bond A 6x1000mm up to 35kg, silver

Approved safety bond

Art. No.: 58010330

GTIN: 4026397607116



The article is no longer in our assortment.

Description:

EUROLITE Safety bonds

The EUROLITE safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The safety bonds are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can secure loads above persons with these safety bonds in all areas where the BGV C1 is required.

Logistic

EAN / GTIN: 4026397607116

Weight: 0,20 kg

Length: 0.15 m

Width: 0.12 m

Height: 0.04 m

Features:

Approved safety bond

- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE Steel Rope 1000x6mm silver with Thimble

Installation rope, safety bond, safety

- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03

- Rope with thimble
- For further information about this product, please refer to the Data Sheet under "Downloads"

EUROLITE Quick Link Type A-200

Quick link

- Complies with DIN 56927:2009-03
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Secured weight (BGV C1):	Max. 35 kg
Strength classification:	1770
Temperature range:	-40° C - +100° C
Weight:	220 g

EUROLITE Steel Rope 1000x6mm silver with Thimble

Maximum load WLL (5-fold):	400 kg
Design of the core:	6 x 19 FC
Strength classification:	1960
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strength of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 1 m Diameter: Ø 6 mm
Weight:	190 g
Length weight:	0,0554 kg/m

EUROLITE Quick Link Type A-200

Maximum load WLL (10-fold):	200 kg
Standard:	DIN 56927:2009-03,
Shape:	A - small opening
Material:	Steel, zinc-plated
Opening:	0-7,5 mm
Dimensions:	Length: 4,50 cm Width: 5,80 cm Depth: 2,70 cm Diameter: Ø 6 mm
Weight:	30 g