

EUROLITE Steel Rope (SC) 600x3mm black with thimbles

Installation rope, safety bond, safety

Art. No.: 5801049B

GTIN: 4026397610390



List price: 4.17 €

incl. 19% VAT.

Description:

EUROLITE Lifting ropes, safety bonds

The EUROLITE lifting ropes, safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The lifting ropes, safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The lifting ropes, safety bonds are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can install and secure loads above persons with these lifting ropes, safety bonds in all areas where the BGV C1 is required.

Use as attachment gear

These ropes are stamped with a WLL describing the maximum load when used for general lifting purposes. For all areas where the BGV C1 is required, the correct lifting rope must be selected only by table 2 of BGI 810-3:2007-03. According to this table, the maximum load of this rope is 40 kg (single-stranded).

Use as safety bond

The correct safety bond must be selected only by table 9 of BGI 810-3:2007-03. According to this table, the maximum load of this safety bond is 5 kg.

Logistic

EAN / GTIN: 4026397610390

Weight: 0,05 kg

Length: 0.09 m

Width: 0.07 m

Height: 0.03 m

Features:

- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Suitable for installing and securing loads above persons
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble

Technical specifications:

Maximum load WLL (5-fold):	100 kg
Design of the core:	6 x 19 WSC
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm ²
Wire surface:	Zinc-plated
Color:	Black
Temperature range:	-40° C - +100° C
Dimensions:	Length: 60 cm Diameter: Ø 3 mm
Weight:	50 g
Length weigth:	0,0311 kg/m