

## EUROLITE STC-550/180 Truss Lifter TÜV/GS

Rugged truss lifter for medium-heavy loads

Art. No.: 59007060

GTIN: 4026397277937



**The article is no longer in our assortment.**

### Description:

The EUROLITE STC-series are truss lifters manufactured under strict TÜV monitoring. These lifts boast of high quality, extraordinary ruggedness, highest versatility and high stability. The production is monitored by the German TÜV SÜD which means that they comply with the highest safety standards.

The GS mark signals to the buyer, customer, or consumer that the chosen product as well as the user manual and production (process) have been tested by an authorized institution such as TÜV SÜD, with priority being given to aspects of safety. In the meantime, the German GS-mark has been recognized as one of the crucial marks within product safety.

### Features:

- Four-part telescopic lifter with galvanized steel sections
- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety bolt for mechanical locking
- Four massive outriggers for highest stability
- Outriggers are firmly connected with the base, the finishing is velcro-protected
- Uneven grounds can be compensated via individually adjustable levelling braces
- Four auto-levelling, galvanized foot plates
- Powder-coated base and galvanized sections for highest corrosion protection
- Complies with DIN EN ISO 12100-2 and DIN 15560-27
- Adjustable height
- 4 castors with 2 locking brakes
- TÜV/GS certified

### Logistic

EAN / GTIN: 4026397277937

Weight: 115,60 kg

Length: 1.85 m

Width: 0.51 m

Height: 0.53 m

Bulky product

## Technical specifications:

---

Maximum carrying capacity:	180 kg
Minimum load:	25 kg
Standard:	DIN EN ISO 12100-2, DIN 15560-27
Height:	Maximum: 550 cm above 4 sections Minimum: 177 cm
Attachment system:	55mm x 55mm
Steel rope:	Ø 5 mm
Type (general stands):	Truss lifter
Transport aid:	4 x castors with 2 locking brakes
Material:	Steel, 2 mm
Transport dimensions:	1,77 m x 60 cm x 46 cm
Base area:	Ø 2,17 m
Weight:	107,00 kg

---