

EUROLITE DPX-1210 DMX dimmer pack

PRO digital 12-channel modular dimmer pack

Art. No.: 70064140

GTIN: 4026397185645



The article is no longer in our assortment.

Features:

- 12-channel dimmer pack with up to 10 A output per channel
- Modular design of the individual dimmer modules, the control module, and the connection module for quick and easy change
- 3-phase or 1-phase power supply
- DMX512 control or analog control
- Synchronization of several DPX-1210 possible via DMX
- Adjustable lamp preheat (0-50%) to prolong bulb life assignable to each channel
- Dimmer curves (linear, square, switch) assignable to each channel
- DMX fail function: automatic digital input check to detect DMX signal errors
- 12 built-in programs with adjustable speed
- Manual mode for dimming capability without an external lighting controller
- LCD
- Automatic circuit breaker per channel (type C)
- Channel outputs on the rear panel pole connectors
- 16-pin industrial sockets connection option (not included)
- Rack installation
- Only for professional use
- Control via stand-alone; DMX

Logistic

EAN / GTIN: 4026397185645

Weight: 28,85 kg

Length: 0.60 m

Width: 0.59 m

Height: 0.33 m

Technical specifications:

Output power: Max. 2300 W per channel
Max. 27600 W

DMX channels: 12

Control:	Stand-alone; DMX
Control channels:	12
Color:	Black
Dimensions:	Width: 48,3 cm Depth: 48,5 cm Height: 17,8 cm
Weight:	25,90 kg
Power supply:	230-380 V AC, 50 Hz
Max. power output:	27600 W
Max. current:	120 A
Number of control channels:	12
Max. output/channel:	2300 W
Max. current/channel:	10 A
Integrated programs:	12
DMX output:	3-pin female XLR socket
DMX input:	3-pin male XLR socket
Analog input:	15-pin Sub-D socket, 12 channels, 0-10 V DC
Power input:	Terminal block/PG cable screw
Fuse:	12 x C 10 A, 230 V
Dimensions (W x D x H):	482 x 485 x 176 mm Rack installation with 4 U
Minimum mounting depth:	500 mm