

EUROLITE DPMX-1216 S DMX Dimmer Pack

12 x 16A dimmer, service friendly modules, 12 safety sockets

Art. No.: 70064182

GTIN: 4026397521764



List price: 1248.31 €

incl. 19% VAT.

Description:

Reliability is always important. Especially at professional events the breakdown of any part of the equipment cannot be accepted. The DPMX-1216 dimmer pack series is the right answer here because it plays it safe: this universal output stage has an automatic circuit breaker on every channel, so single failures can be corrected without causing a complete blackout. Another benefit are the different outputs. Pole connector, safety plug, CEE or multipin: the DPMX-1216 19" serves really any kind.

Logistic

EAN / GTIN: 4026397521764

Weight: 20,45 kg

Length: 0.61 m

Width: 0.56 m

Height: 0.30 m

Features:

- 12-channel dimmer pack with up to 16 A output per channel
- Modular design of the individual dimmer modules for quick and easy change
- 3-phase or 1-phase power supply
- Adjustable lamp preheat (0-50%) and limiter function to prolong bulb life
- Curve function for selection of different fade modes
- Dim or switch option assignable to each channel
- DMX Fail function: automatic digital input check to detect DMX signal errors
- Manual mode for dimming capability without an external lighting controller
- Synchronization of several devices possible via DMX
- Automatic circuit breaker per channel (type C)
- Channel outputs on the rear panel via safety sockets
- Only for professional use
- 12 integrated show programs
- Preprogrammed 12 scenes/chases ()
- Control via stand-alone; DMX
- (19") 48.3 cm rack installation 4 U
- For application areas such as: Trade fair and shop fitting; Stage; theater; Rental

- Very quiet working noise
- Package contents**
- 1 x device, 1 x user manual

Technical specifications:

Power supply:	230/380 V AC, 50 Hz
Output power:	Max. 43470 W Max. 3680 W per channel
Output current:	Max. 189 A
Power connection:	Mains input via screw terminal
Power output:	12 x Safety contact (F), hinged lid mounting version
Power output fuse per channel:	C 16 A Fuse resettable
Programs:	Preprogrammed 12 scenes/chases)
DMX channels:	12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX
Control channels:	12
Color:	Black
Housing design:	(19") 48.3 cm rack installation 4 U
Dimensions:	Width: 48,3 cm Depth: 52,0 cm Height: 17,8 cm
Weight:	17,70 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)